

Public Hague Platform API version v1

http://TBD/webservices/offices/api/{version}

The Hague System for the International Registration of Industrial Designs provides a practical business solution for registering up to 100 designs in 76 Contracting Parties, covering 93 countries, through the filing of a single international application.

Public Hague API: March 2023

- **version:** *required*(v1)


/pingMe

/pingMe

GET 

GET  /pingMe

Hello message with the provided name(nothing if name not provided)

 Secured by **oauth_2_0**

Public Hague services supports OAuth 2.0 for authenticating all API requests.

Request

Query Parameters

- **name:** *(string)*

Response

HTTP status code **200**

Hello message received successfully

Body

Media type: application/xml

Type: any

Security

Secured by **oauth_2_0**

Headers

- **Authorization:** *required*(string)
Used to send a valid OAuth 2 access token.

HTTP status code **401**

Unauthorized access. This can happen if the user's access token is not present or the access token is wrong, or expired, etc.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>401000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access not authorized because idToken is not found in the request. Authentication is required in order to call a service from HBO. Add a header in the request with name: 'Authorization' and value: 'Bearer + idToken'</com:TransactionErrorText>
</com:TransactionError>
```

HTTP status code 403

Forbidden request. This can happen when user is authenticated to use the service but is not authorized for the specific resource requested.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>403000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access forbidden to the requested resource</com:TransactionErrorText>
</com:TransactionError>
```

/request

/request

POST

POST **/request**

Create a new service request from imported file identified by **serviceRequestId**.

- **serviceRequestId:** Unique identifier for the service request generated by HBO

In order to create a new service request, the information must be sent as a zip file.

The content of the zip will be:

- ST.96(xml file)
- images(folder with images)
- docs(folder with documents)

An example file could be found at: ftp://ftpird.wipo.int/wipo/hague/ST96_V_4_0_test/import-packages-4.0.zip

As a result, an importId will be returned. This importId will be used after for asking import information via an endpoint created for that

Information about import status for a specific file could be retrieved as follow:

- {baseUri}/request/import/{importId}

Note: A single service request will be processed at a time. If there are more than one, a bad request error will be raised.

Secured by **oauth_2_0**

Public Hague services supports OAuth 2.0 for authenticating all API requests.

Request

Body

body

Media type: multipart/form-data

Type: object

Properties

- **file:** *required(file)*
The file to be uploaded

Response

HTTP status code [202](#)

importId: Id generated from HBO to uniquely identify the imported file.

File has been received and it will be imported. You will be able to query the import information status by accessing `/request/import/{importId}`

Body

Media type: application/xml

Type: array of ImportProcessingStage

Items: ImportProcessingStage

- **DocumentIdentifier:** *required(string)*
Import identifier
- **FileName:** *required(string)*
Imported file's name
- **RequestIdentifier:** *(integer)*
Service request id generated in HBO as a result of importing a file
- **ImportProcessingStageCategory:** *required(one of UNDEFINED, WAITING, SUCCESS, ERROR)*
Import information status
 - **UNDEFINED:** Import id was not found and no extra information is available from HBO.
 - **WAITING:** Import id was found in HBO, but file still waiting to be imported.
 - **SUCCESS:** Import id was found in HBO and file was already imported. The **RequestIdentifier** field contains the id generated by HBO to indicate a request creation as a result of the file import process.
 - **ERROR:** import id was not found in HBO, an error happened during the file import process.
- **CommentText:** *required(string)*
Human readable information about import status
- **OfficeSpecificContent:** *(string)*
Extra information, for those cases where more information is required
- **AuthenticatedUserIdentifier:** *(string)*
ClientId that did the import
- **DocumentReceivedDateTime:** *(datetime-only)*
Date and time when import file was received
- **DocumentImportedDateTime:** *(datetime-only)*
Date and time when the file was imported

Example:

```
<dgn:HagueWebApiResponse dgn:Application="eHagueDev" dgn:Caller="KR" dgn:TimeEnd="2021-09-15T14:33:31.158" dgn:TimeStart="2021-09-15T14:33:30.601" dgn:UUID="4115d5b6370ad163" xmlns:com="http://www.wipo.int/standards/XMLSchema/ST96/Common" xmlns:dgn="http://www.wipo.int/standards/XMLSchema/ST96/Design" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Design http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Design/Flatten/HagueIBToOfficeTransaction_V4_0.xsd">
  <dgn:ImportProcessingStageBag>
    <dgn:ImportProcessingStage>
      <com:DocumentIdentifier>123456</com:DocumentIdentifier>
      <com:FileName>application-single</com:FileName>
      <com:RequestIdentifier>970000032</com:RequestIdentifier>
      <dgn:ImportProcessingStageCategory>Success</dgn:ImportProcessingStageCategory>
      <com:CommentText>File bound to import id has been imported successfully</com:CommentText>
      <dgn:AuthenticatedUserIdentifier>clientId</dgn:AuthenticatedUserIdentifier>
      <dgn:DocumentReceivedDateTime>2021-07-26T09:27:28</dgn:DocumentReceivedDateTime>
      <dgn:DocumentImportedDateTime>2021-07-26T09:27:48.316</dgn:DocumentImportedDateTime>
    </dgn:ImportProcessingStage>
  </dgn:ImportProcessingStageBag>
</dgn:HagueWebApiResponse>
```

HTTP status code 400

Bad request. Information sent is not correct.

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>400000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Field id is required</com:TransactionErrorText>
</com:TransactionError>
```

HTTP status code 500

Unknown error on server side

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>500000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">
    Unkonwn error. Connection timeOut.
  </com:TransactionErrorText>
</com:TransactionError>
```

Security

Secured by oauth_2_0

Headers

- **Authorization:** *required(string)*
Used to send a valid OAuth 2 access token.

HTTP status code 401

Unauthorized access. This can happen if the user's access token is not present or the access token is wrong, or expired, etc.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>401000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access not authorized because idToken is not found in the request. Authentication is required in order to call a service from HBO. Add a header in the request with name: 'Authorization' and value: 'Bearer + idToken'</com:TransactionErrorText>
</com:TransactionError>
```

HTTP status code 403

Forbidden request. This can happen when user is authenticated to use the service but is not authorized for the specific resource requested.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>403000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access forbidden to the requested resource</com:TransactionErrorText>
</com:TransactionError>
```

/request/{serviceRequestId}

GET 

GET  /request/{serviceRequestId}

Retrieve information regarding a service request referenced by **serviceRequestId**.

Secured by **oauth_2_0**

Public Hague services supports OAuth 2.0 for authenticating all API requests.

Request

URI Parameters

- **serviceRequestId:** *required(string)*
Unique identifier generated by HBO to identify the service request.

Query Parameters

- **format:** *(string)*
Unique identifier used to identify the ST.96 format (default ST96_V4).
The format must be one of the following options:
 - ST94_V4 (default)
 - ST94_V7

Response

HTTP status code **200**

Service request status in ST.96 format. Response in ST.96 format pending definition.
Despite response returning a list, in this case, the list would be up to 1 entry.
Response is wrapped by **HagueWebApiResponse**.

Body

Media type: application/xml

Type: array of RequestProcessingStage

Items: RequestProcessingStage

- **RequestIdentifier:** *required(string)*
Service request ID generated in HBO
- **HagueIBToOfficeRequestCategory:** *required(one of APPLICATION, GRANT_PROTECTION, REFUSAL, REFUSAL_WITHDRAWAL, INVALIDATION, DIVISION, SECOND_PART_FEE_PAYABLE, SECOND_PART_FEE_PAID, CANCELLATION_NON_PAYMENT, REFUSAL_OWNER_CHANGE, REFUSAL_WITHDRAWAL_OWNER_CHANGE, REFUSAL_CORRECTION, OTHER)*
Service request processing stage
- **RequestProcessingStageCategory:** *required(one of UNDER_EXAMINATION, PENDING_REGULARIZATION, RECORDED, ABANDONED, CANCELLED)*
Service request processing stage
Import information status
 - **UNDER_EXAMINATION:** Service request is being examined
 - **PENDING_REGULARIZATION:** Service request is waiting for regularization. Pending action from customer
 - **RECORDED** Service request was received successfully and is already recorded
 - **ABANDONED** Service request has been abandoned
 - **CANCELLED** Service request has been cancelled
- **InternationalRegistrationNumberBag:** *(object)*
List of IRNs affected by the service request
 - **InternationalRegistrationNumber:** *(string)*
IRN affected by the service request
- **RecordIdentifier:** *(integer)*
Record identifier generated in HBO
- **InternationalRecordingDate:** *(date-only)*
Date when record was recorded
- **PublicationDate:** *(date-only)*
Date when record was published

Example:

```
<dgn:HagueWebApiResponse dgn:Application="eHagueDev" dgn:Caller="KR" dgn:TimeEnd="2021-09-15T14:13:13.078" dgn:TimeStart="2021-09-15T14:13:12.467" dgn:UUID="e3645f34e8868dc5" xmlns:com="http://www.wipo.int/standards/XMLSchema/ST96/Common" xmlns:dgn="http://www.wipo.int/standards/XMLSchema/ST96/Design" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Design http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Design/Flatten/HagueIBToOfficeTransaction_V4_0.xsd">
  <dgn:RequestProcessingStageBag>
    <dgn:RequestProcessingStage>
      <com:RequestIdentifier>970000034</com:RequestIdentifier>
      <dgn:HagueIBToOfficeRequestCategory>Application</dgn:HagueIBToOfficeRequestCategory>
      <dgn:RequestProcessingStageCategory>Recorded</dgn:RequestProcessingStageCategory>
      <com:InternationalRegistrationNumberBag>
        <com:InternationalRegistrationNumber>DM/200003</com:InternationalRegistrationNumber>
      </com:InternationalRegistrationNumberBag>
      <com:RecordIdentifier>970000007</com:RecordIdentifier>
      <com:InternationalRecordingDate>2021-08-17</com:InternationalRecordingDate>
    </dgn:RequestProcessingStage>
  </dgn:RequestProcessingStageBag>
</dgn:HagueWebApiResponse>
```

HTTP status code 404

Service request identified by officeRef does not exist

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>404000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Entity not found</com:TransactionErrorText>
</com:TransactionError>
```

HTTP status code 500

Unknown error on server side

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>500000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">
    Unkonwn error. Connection timeOut.
  </com:TransactionErrorText>
</com:TransactionError>
```

Security

Secured by oauth_2_0

Headers

- **Authorization:** *required(string)*
Used to send a valid OAuth 2 access token.

HTTP status code 401

Unauthorized access. This can happen if the user's access token is not present or the access token is wrong, or expired, etc.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>401000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access not authorized because idToken is not found in the request. Authentication is required in order to call a service from HBO. Add a header in the request with name: 'Authorization' and value: 'Bearer + idToken'</com:TransactionErrorText>
</com:TransactionError>
```

HTTP status code 403

Forbidden request. This can happen when user is authenticated to use the service but is not authorized for the specific resource requested.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>403000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access forbidden to the requested resource</com:TransactionErrorText>
</com:TransactionError>
```

/request/import/{importId}

GET 

GET  /request/import/{importId}

Retrieve import information about an ST.96 file sent to HBO for generating a service request referenced by **importId**.

Secured by **oauth_2_0**

Public Hague services supports OAuth 2.0 for authenticating all API requests.

Request

URI Parameters

- **importId:** *required(string)*
Unique identifier generated by HBO at import request time.

Query Parameters

- **format:** *(string)*
Unique string used to identify the ST.96 format (default ST96_V4).
The format must be one of the following options:
 - ST94_V4 (default)
 - ST94_V7

Response

HTTP status code **200**

Service request status in ST.96 format. Response in ST.96 format pending definition.
Despite response returning a list, in this case, the list would be up to 1 entry.
Response is wrapped by **HagueWebApiResponse**.

Body

Media type: application/xml

Type: array of ImportProcessingStage

Items: ImportProcessingStage

- **DocumentIdentifier:** *required(string)*
Import identifier
- **FileName:** *required(string)*
Imported file's name
- **RequestIdentifier:** *(integer)*
Service request id generated in HBO as a result of importing a file
- **ImportProcessingStageCategory:** *required(one of UNDEFINED, WAITING, SUCCESS, ERROR)*
Import information status
 - **UNDEFINED:** Import id was not found and no extra information is available from HBO.
 - **WAITING:** Import id was found in HBO, but file still waiting to be imported.
 - **SUCCESS:** Import id was found in HBO and file was already imported. The **RequestIdentifier** field contains the id generated by HBO to indicate a request creation as a result of the file import process.
 - **ERROR:** import id was not found in HBO, an error happened during the file import process.
- **CommentText:** *required(string)*
Human readable information about import status
- **OfficeSpecificContent:** *(string)*
Extra information, for those cases where more information is required
- **AuthenticatedUserIdentifier:** *(string)*
ClientId that did the import
- **DocumentReceivedDateTime:** *(datetime-only)*
Date and time when import file was received
- **DocumentImportedDateTime:** *(datetime-only)*
Date and time when the file was imported

Example:

```
<dgn:HagueWebApiResponse dgn:Application="eHagueDev" dgn:Caller="KR" dgn:TimeEnd="2021-09-15T14:33:31.158" dgn:TimeStart="2021-09-15T14:33:30.601" dgn:UUID="4115d5b6370ad163" xmlns:com="http://www.wipo.int/standards/XMLSchema/ST96/Common" xmlns:dgn="http://www.wipo.int/standards/XMLSchema/ST96/Design" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Design http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Design/Flatten/HagueIBToOfficeTransaction_V4_0.xsd">
  <dgn:ImportProcessingStageBag>
    <dgn:ImportProcessingStage>
      <com:DocumentIdentifier>123456</com:DocumentIdentifier>
      <com:FileName>application-single</com:FileName>
      <com:RequestIdentifier>970000032</com:RequestIdentifier>
      <dgn:ImportProcessingStageCategory>Success</dgn:ImportProcessingStageCategory>
      <com:CommentText>File bound to import id has been imported successfully</com:CommentText>
      <dgn:AuthenticatedUserIdentifier>clientId</dgn:AuthenticatedUserIdentifier>
      <dgn:DocumentReceivedDateTime>2021-07-26T09:27:28</dgn:DocumentReceivedDateTime>
      <dgn:DocumentImportedDateTime>2021-07-26T09:27:48.316</dgn:DocumentImportedDateTime>
    </dgn:ImportProcessingStage>
  </dgn:ImportProcessingStageBag>
</dgn:HagueWebApiResponse>
```

HTTP status code 500

Unknown error on server side

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>500000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">
    Unkonwn error. Connection timeOut.
  </com:TransactionErrorText>
</com:TransactionError>
```

Security

Secured by oauth_2_0

Headers

- **Authorization:** *required*(*string*)
Used to send a valid OAuth 2 access token.

HTTP status code 401

Unauthorized access. This can happen if the user's access token is not present or the access token is wrong, or expired, etc.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>401000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access not authorized because idToken is not found in the request. Authentication is required in order to call a service from HBO. Add a header in the request with name: 'Authorization' and value: 'Bearer + idToken'</com:TransactionErrorText>
</com:TransactionError>
```

HTTP status code 403

Forbidden request. This can happen when user is authenticated to use the service but is not authorized for the specific resource requested.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>403000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access forbidden to the requested resource</com:TransactionErrorText>
</com:TransactionError>
```


/publication

/publication/bulletin/{weekId}

GET 

GET  /publication/bulletin/{weekId}

Get Bulletin for a specific week identified by **weekId**

 Secured by **oauth_2_0**

Public Hague services supports OAuth 2.0 for authenticating all API requests.

Request

URI Parameters

- **weekId:** *required(string)*
Unique string used to identify the Bulletin week.
The format must be YYYYWW. For instance: 202010
 - YYYY represents the year
 - WW represents the week of the year

Query Parameters

- **format:** *(string)*
Unique string used to identify the ST.96 format (default ST96_V4).
The format must be one of the following options:
 - ST94_V4 (default)
 - ST94_V7

Response

HTTP status code 302

URL redirection to access the Bulletin information for a week in ST.96.
URL is informed in redirect header and in the body.
Authorization header is also required in the request to redirection URL obtained as response.

Body

Media type: application/xml

Type: string

HTTP status code 400

Bad request. Information sent is not correct.

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">  
  <com:TransactionErrorCode>400000</com:TransactionErrorCode>  
  <com:TransactionErrorText com:languageCode="en">Field id is required</com:TransactionErrorText  
>
```

HTTP status code 404

Service request identified by officeRef does not exist

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">  
  <com:TransactionErrorCode>404000</com:TransactionErrorCode>  
  <com:TransactionErrorText com:languageCode="en">Entity not found</com:TransactionErrorText>  
</com:TransactionError>
```

HTTP status code 500

Unknown error on server side

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** *(string)*
Error code
- **TransactionErrorText:** *(object)*
Error description
 - **languageCode:** *(string)*
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">  
  <com:TransactionErrorCode>500000</com:TransactionErrorCode>  
  <com:TransactionErrorText com:languageCode="en">  
    Unkonwn error. Connection timeOut.  
  </com:TransactionErrorText>  
</com:TransactionError>
```

Security

Secured by oauth_2_0

Headers

- **Authorization:** *required(string)*
Used to send a valid OAuth 2 access token.

HTTP status code 401

Unauthorized access. This can happen if the user's access token is not present or the access token is wrong, or expired, etc.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">  
  <com:TransactionErrorCode>401000</com:TransactionErrorCode>  
  <com:TransactionErrorText com:languageCode="en">Access not authorized because idToken is not found in the request. Authentication is required in order to call a service from HBO. Add a header in the request with name: 'Authorization' and value: 'Bearer + idToken'</com:TransactionErrorText>  
</com:TransactionError>
```

HTTP status code 403

Forbidden request. This can happen when user is authenticated to use the service but is not authorized for the specific resource requested.

Body

Media type: application/xml

Type: any

Example:


```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>403000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access forbidden to the requested resource</com:TransactionErrorText>
</com:TransactionError>
```

/publication/copy/confidential/{weekId}

GET 

GET  /publication/copy/confidential/{weekId}

Get confidentialCopy for a specific week identified by **weekId**.
Office will be inferred from caller.

 Secured by **oauth_2_0**

Public Hague services supports OAuth 2.0 for authenticating all API requests.

Request

URI Parameters

- **weekId:** *required(string)*
Unique string used to identify the Bulletin week.
The format must be YYYYWW. For instance: 202010
 - YYYY represents the year
 - WW represents the week of the year

Query Parameters

- **format:** *(string)*
Unique string used to identify the ST.96 format (default ST96_V4).
The format must be one of the following options:
 - ST94_V4 (default)
 - ST94_V7

Response

HTTP status code **302**

URL redirection to access the confidentialCopy information for a week in ST.96.
URL is informed in redirect header and in the body.
Authorization header is also required in the request to redirection URL obtained as response.

Body

Media type: application/xml

Type: string

HTTP status code **400**

Bad request. Information sent is not correct.

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>400000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Field id is required</com:TransactionErrorText
>
```

HTTP status code **404**

Service request identified by officeRef does not exist

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>404000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Entity not found</com:TransactionErrorText>
</com:TransactionError>
```

HTTP status code **500**

Unknown error on server side

Body

Media type: application/xml

Type: object

Properties

- **TransactionErrorCode:** (*string*)
Error code
- **TransactionErrorText:** (*object*)
Error description
 - **languageCode:** (*string*)
Language code in which the text is

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>500000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">
    Unkonwn error. Connection timeOut.
  </com:TransactionErrorText>
</com:TransactionError>
```

Security

Secured by oauth_2_0

Headers

- **Authorization:** *required*(string)
Used to send a valid OAuth 2 access token.

HTTP status code 401

Unauthorized access. This can happen if the user's access token is not present or the access token is wrong, or expired, etc.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>401000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access not authorized because idToken is not found in the request. Authentication is required in order to call a service from HBO. Add a header in the request with name: 'Authorization' and value: 'Bearer + idToken'</com:TransactionErrorText>
</com:TransactionError>
```

HTTP status code 403

Forbidden request. This can happen when user is authenticated to use the service but is not authorized for the specific resource requested.

Body

Media type: application/xml

Type: any

Example:

```
<com:TransactionError xsi:schemaLocation="http://www.wipo.int/standards/XMLSchema/ST96/Common http://www.wipo.int/standards/XMLSchema/ST96/V4_0/Common/TransactionError.xsd">
  <com:TransactionErrorCode>403000</com:TransactionErrorCode>
  <com:TransactionErrorText com:languageCode="en">Access forbidden to the requested resource</com:TransactionErrorText>
</com:TransactionError>
```